

# Vfp SERIES

FINE PITCH FIXED INSTALLATION



PIXEL PITCH	0.94mm		1.25mm		1.56mm		1.87mm		2.5mm		
MODEL NAME	Vfp0.9	Vfp0.9r	Vfp1.2	Vfp1.2r	Vfp1.5	Vfp1.5r	Vfp1.8	Vfp1.8r	Vfp2.5	Vfp2.5r	Vfp2.5B
PIXELS PER CABINET	640 x 360 (230,400)		480 x 270 (129,600)		384 x 216 (82,944)		320 x 180 (57,600)		240 x 135 (32,400)		240 x 135 (32,400)
LED DRIVER IC	Chipone ICND2069		Chipone ICND2065		Chipone ICND2065		Chipone ICND2055		Macroblock MBI5253		Macroblock MBI5253
RECEIVING CARD (QUANTITY)	NovaStar A10s Pro		NovaStar A8s		NovaStar A8s		NovaStar A8s		NovaStar A8s		Brompton
	1 card	2 cards	1 card	2 cards	1 card	2 cards	1 card	2 cards	1 card	2 cards	1 card
BRIGHTNESS	≥600 NITS		≥600 NITS		≥600 NITS		≥600 NITS		≥1200 NITS		≥1200 NITS
CABINET WEIGHT	11.66 lbs	12.76 lbs	11.66 lbs	12.76 lbs	11.66 lbs	12.76 lbs	11.66 lbs	12.76 lbs	11.66 lbs	12.76 lbs	11.66 lbs
CABINET MATERIAL	Aluminum						Aluminum				
CABINET SIZE	600mm (W) / 337.5mm (H) / 40mm (D)						600mm (W) / 337.5mm (H) / 40mm (D)				
MODULE SIZE	150mm x 168.75mm						150mm x 168.75mm				
LED TYPE	Nationstar Gold Wire						Nationstar Gold Wire				
REFRESH RATE	≥3840 Hz						≥3840 Hz				
GRayscale	≥14 bits						≥14 bits				
VIEWING ANGLE	160° Horizontal & 160° Vertical						160° Horizontal & 160° Vertical				
SERVICE ACCESS	Front						Front				
CURVE	Yes - With Optional Brackets						Yes - With Optional Brackets				
IP RATING	IP30						IP30				
VOLTAGE RANGE	110-240 VAC 50-60Hz						110-240 VAC 50-60Hz				
AVG. POWER DRAW	.21A@208 .39A@110	.22A@208 .41A@110	.20A@208 .37A@110	.20A@208 .38A@110	.20A@208 .38A@110	.21A@208 .39A@110	.19A@208 .35A@110	.20A@208 .37A@110	.17A@208 .32A@110	.18A@208 .34A@110	.17A@208 .32A@110
MAX POWER DRAW	.65A@208 1.23A@110	.67A@208 1.26A@110	.63A@208 1.20A@110	.65A@208 1.24A@110	.63A@208 1.18A@110	.65A@208 1.23A@110	.62A@208 1.16A@110	.63A@208 1.20A@110	.60A@208 1.14A@110	.63A@208 1.18A@110	.60A@208 1.14A@110